

VOSM350 Evaluation Kit

A comprehensive tool kit for development of embedded products to implement industrial IoT applications

Overview


VOSM350 evaluation kit is designed for programmers or developers who seek to reduce the time-to-market of embedded products with a comprehensive tool kit. The evaluation kit features a VOSM350 evaluation board and a TMO070 open-frame touchscreen monitor.

The VOSM350 evaluation board is powered by MediaTek G350 chipset, which integrates a quad-core Arm Cortex-A53 processor, a Mali-G52 GPU, a VP6 APU for AI and computer vision algorithms and a HiFi4 audio engine DSP to fit for edge AI applications that require voice and vision processing. Its support for Wi-Fi and Bluetooth wireless connectivity functions increases its versatility for IoT scenarios. Additionally, it offers rich interfaces to allow connection of diverse peripherals for debugging the module and the device itself.


The TMO070 open-frame touchscreen monitor applies a 7-inch multi-point PCAP touch screen and features quick response time, large visible area and viewing angle. It is designed to deliver excellent visual experience and improve human-machine interaction accuracy.

Accessories available in the kit


- VOSM350 evaluation board (carrier board + SOM)
- TMO070 open-frame touchscreen monitor
- Power adapters (5V DC for the board¹, 12V DC for the touchscreen monitor)
- Touch USB cable
- HDMI cable



Exterior



VOSM350 evaluation board



TMO070 Touchscreen monitor

Features and benefits

- Rich interfaces on the evaluation board for diverse peripherals
- Android and Linux systems supported
- Extended service life (7+ years)
- 7" TFT LCD, 300 nits, 1024 x 600
- Scalable platform


¹ A USB-C to dual USB-A male extension cable is used to connect both the power adapter and host PC for supplying power and debugging the board, respectively.

Evaluation Kit Datasheet


VOSM350 Evaluation Board				
System	CPU	MTK G350, ARM Cortex-A53, Quad-Core Low Power Processor, Max 2.0GHz Mali-G52 GPU,600MHz		
	Memory	4GB LPDDR4		
	Storage	32GB eMMC 5.1		
	EEPROM	2Kb (for hardware configuration information)		
	PMIC	MT6390		
Communication	Ethernet	1 x RJ45, 10M/100Mbps		
	Wi-Fi & Bluetooth	802.11 a/b/g/n/ac + Bluetooth 5.0		
Media	Video processing	Dual displays, FHD60/HD60, 1080p60, H.265/H.264/VP9		
	Audio DSP	HiFi-4		
	Camera	2 x Camera (Max.)		
I/Os	Display	1 x 4-lane MIPI DSI / 1 x HDMI		
	MIPI CSI	1 x 4-lane MIPI CSI / 2 x 2-lane MIPI CSI		
	Audio	1 x Earphone jack	1 x Speaker connector	
		1 x DMIC		
	USB	1 x USB Type-A	1 x USB Type-C (USB 2.0 OTG supported)	
	I ² C	2 x I ² C		
	UART	1 x Debug UART (1.8V level)	2 x Communication UART (TTL)	
	GPIO	25 x GPIO (max.)		
	SD slot	2 x SD slot		
	Key	1 x Power key		
	JTAG	Supported		
	PWM	Supported		
	Power	Input	5V/1A DC input	
Software	Operating system	Android 10+	Optional: Yocto	
	Device management	BlueSphere MDM (Android version only)		
	Upgrade tool	BlueSphere OTA		
Mechanical	Dimensions	142mm x 90mm x 18.84mm (EVB)	45mm x 45mm x 1.2mm (SOM)	
Environment Condition	Temperature	Operating: -20°C ~ +60°C	Storage: -30°C ~ +70°C	
	Humidity	≤95% RH (Non-condensing)		
	Certification	CE, FCC, CCC		
TMO070 Open-frame Touchscreen Monitor				
Display	Diagonal size	7" TFT LCD with LED backlight		
	Aspect ratio	16:9		
	Resolution	1024 x 600		
	Brightness	300 nits		
	Active area	154.21mm × 85.92mm		
	Contrast ratio	800:1		
	Number of colors	16.7M		
	Response time	25ms		
	Viewing angle	Horizontal: 150°	Vertical: 140°	
Touch panel	Touch point	5-point PCAP touchscreen		
	Touch control	Finger, stylus pen		
	Cover lens thickness	1.1mm		
	Surface treatment	Anti-fingerprint, tempered glass	Optional: Anti-glare / Anti-reflection	
	Light transmittance ratio	>85%		
Video	Touch communication interface	USB 2.0 Type-B		
	Video interface	1 x VGA	1 x HDMI	
Mechanical	Dimensions	186.2mm x 119.9mm x 35.7mm (without brackets)		
	Weight	0.9kg		
	Installation	VESA mounting (50mm x 50mm)	Side bracket mounting	
	OSD	Built-in OSD (set up with OSD keys)	Controls: Menu, Up, Down, Back, Power	
Software	Power input	12V DC		
	Power consumption	<6W		
	Adjustment of brightness, contrast, color temp.	Supported		
Environment Condition	Temperature	Operating: 0°C ~ +40°C	Storage: -20°C ~ +60°C	
	Humidity	10%~90% RH (non-condensing)		
	MTBF	50,000 hours		
	Warranty	3 years		
	ESD	ESD: ±4KV (contact) and ±8KV (air)		
	Certificate	CCC, FCC, CE, UL		

Wiring

1. Use the HDMI cable and touch USB cable to connect the touchscreen monitor and the evaluation board for display and touch purposes, respectively;



2. Connect the 12V DC power supply to the touchscreen monitor. Plug the main USB-A port of the USB-C to dual USB-A male extension cable into the host PC (if necessary), the auxiliary USB-A port to the 5V DC adapter, and the USB-C into the evaluation board for debugging and charging purposes;



3. Plug the adapters separately into proper outlets to power on the devices.

Company Profile

Since its establishment in 2002 by two Silicon Valley entrepreneurs, Vantron Technology has been at the forefront of the connected IoT devices and IoT platform solutions. Today, Vantron boasts a global customer base that includes several Fortune 500 companies. Its product lines cover intelligent edge hardware, IoT communication devices, industrial displays and BlueSphere cloud device management platforms.

With over 20 years of experience in R&D of intelligent edge hardware, Vantron has provided users with diverse embedded solutions featuring ARM and X86 architectures. Its offerings range from Linux to Windows, from embedded level to desktop level, and from gateways to servers. In addition, it provides users with system clipping, driver transplantation and other related services.