# VT-SBC-3568 Single Board Computer



#### **Product Brief**

**Exterior and Features** 

VT-SBC-3568 Single Board Computer is powered by Rockchip RK3568 processor that integrates quad-core ARM Cortex-A55 CPU and Mali G52 GPU to provide optimized performance at lower power consumption, and offer high-quality video encoding and decoding for better display performance.

While both wired and wireless network accesses are available, user data is kept safe and secure in transmission. Meanwhile, the board provides a range of customer expansion options to meet the requirements of different application purposes, especially in industrial IoT scenarios.

Featuring high flexibility and high performance, the board is able to work under extreme environments at industrial-grade temperatures ranging from  $-20^{\circ}$ C to  $+70^{\circ}$ C, making it a reliable industrial IoT solution.



## VT-SBC-3568

命 RK3568, Quad-core ARM Cortex-A55 processor 回 4GB on-board LPDDR4 Rich interfaces, flexible expansion high-quality video encoding and decoding Ø Ethernet/Wi-Fi & BT/4G/5G supported **(–**) RTC and WDT supported Ŷ USB 2.0 & USB 3.0 ₽ Industrial-grade temperature range

### VT-SBC-3568 Single Board Computer Datasheet

| VT-SBC-3568              |                               |  |   |
|--------------------------|-------------------------------|--|---|
| System                   | CPU                           | RK3568, Quad-core ARM Cortex-A55 MPCore, up to 2.0 GHz   |   |
|                          | GPU                           | ARM Mali-G52   |   |
|                          | Memory                        | 4GB LPDDR4 (Optional: 2GB)   |   |
|                          | Storage                       | 16GB eMMC V5.1, up to 128GB<br>2Kb EEPROM  |   |
| Communication            | Ethernet                      | 1 x RJ45, 10/100/1000Mbps 100Base-T4, surge suppression (Optional: 2 x RJ45)                                 |   |
|                          | Cellular                      | 4G/5G (Optional)   |   |
|                          | Wi-Fi & BT                    | 2.4GHz/5GHz Wi-Fi & BT 5.0   |   |
| Media                    | Display                       | 1x Dual LVDS with backlight control, up to $1920x1080$ (Optional: eDP, up to 2K)                             |   |
|                          |                               | 1 x HDMI 2.0   | 1 x MIPI DSI                                |
|                          | Camera                        | 1 x 4-lane MIPI CSI  |   |
|                          | Audio                         | 1 x 3.5mm Audio jack   | $2 \times 5W/8\Omega$ Speaker connector     |
| I/Os                     | Serial                        | 5 x UART (RS232/RS485)   | 1 x UART for debugging                      |
|                          | USB                           | 1 x USB 3.0 Type-A<br>1 x USB 2.0 Type-A   | 1 x USB 2.0 Type-C<br>3 x USB 2.0 connector |
|                          | GPIO                          | 18 x GPIO  |   |
|                          | SIM slot                      | 1 x Micro SIM slot   |   |
|                          | RTC                           | Supported  |   |
|                          | WDT                           | Supported  |   |
| Expansion                | Bus                           | 2 x CAN, without transmitter<br>1 x I <sup>2</sup> C for infrared TP   | 1 x M.2 B-key for 4G/5G module or SSD       |
| System Control           | Button                        | 1 x Reset<br>1 x Power button  | 1 x Volume button                           |
| Power                    | Input                         | 12V/3A DC  |   |
| Software                 | Operating system              | Debian 10, Android 11+   |   |
|                          | Device management<br>platform | BlueSphere MDM (Android device only)   |   |
|                          | OTA tool                      | BlueSphere OTA   |   |
| Mechanical               | Dimensions                    | 146.02mm x 102mm   |   |
|                          | Cooling mode                  | Fanless  |   |
| Environment<br>Condition | Temperature                   | Operating: 0°C~+60°C (RK3568), -20°C~+70°C (RK3568J)<br>Storage: -20°C~+70°C (RK3568), -40°C~+85°C (RK3568J) |   |
|                          | Humidity                      | ≤96%RH (Non-condensing)  |   |

### **Product Outlines**





Vantron | Embedded in your success, Embedded in your better life World-leading provider of embedded/IoT products and solutions

### **Block Diagram**



#### **Company Profile**

Since 2002 established by two Silicon Valley entrepreneurs, Vantron Technology has been a pioneer in connected IoT devices and IoT platform solutions. Today, Vantron serves countless customers all over the world, some of them are Fortune 500 companies. Products lines cover edge intelligent hardware, IoT communication devices, industrial displays and BlueSphere cloud device management platform.

Vantron has 20 years of experience in R&D of embedded edge intelligent hardware like SOM board and motherboard, and provided users with various embedded solutions with ARM and X86 architecture. From Linux to Windows, from embedded to desktop level, from gateway to server. At the same time, we provide our users with system clipping, driver transplantation and other services.

Vantron IoT communication devices support multi-protocol connection of industrial equipment, edge computing of local data. Abundant wired and wireless connectivity make remote operations and maintenance possible. From electricity and transportation to smart retail, medical and warehousing, Vantron IoT communication device can be deployed anywhere in any business section. Vantron believes its IoT solution to help many companies finish their digital transformation, efficiency of manufacturing and productivities have been improved significantly.

Vantron industrial display systems, ARM and X86 series, are equipped with Rockchip, NXP, MediaTek, Intel and other high-performance processors. It supports various operating systems such as Windows, Linux, and Android. Diverse wireless communications keep your device online all the time. Multiple installation methods make it suitable for a variety of application scenarios. Features like waterproof, dustproof, shatter resistant guarantee the best performance in any environment.

Vantron BlueSphere device management platform, a software product, is playing a big role in Vantron overall IoT solution. Today, Vantron puts more focus on offering complete cost effective, leading-edge yet reliable solutions to help customers carry out their visions.

VT-SBC-3568 V2.0 © 2023 Vantron Technology, Inc. All rights reserved. Vantron Technology, Inc. reserves the right to update or modify this document at any time without prior notice